DRY AGING CABINET

OPERATING TEMPERATURE: 0°C +4°C



KLIMA MEAT VISION. PREMIER Control, glass door,



glass back, black

MODEL	DIMENSIONS	DECODIDITION		
MODEL	DIMENSIONS	DESCRIPTION	POWER	CAPACITY KG
KMVS	1100x765x1390h	Glass door and glass back	KW 0,40	min/max 50/120 Kg*
- provided of no	.2 customized s/s fridge racks	•		
•	ne installation assistance inclu			
* Suggested canad	city for a correct working			
Standard equipment:			- Datalogger for HACCP	
- Test centre function			- Sani zer "Oxigenklima»	
- Tropicalised and customized climate class 5 refrigerant			- 20 preset and customizable recipes	
group with Gas R290			- Possibility to set 20 phases per each recipe	
- Display touchscreen 7" with icons			- Temperature humidity and electrical power supply alarm	
Meat colour led lights			management	
- Horizontal and vertical air flow «patented»			- Phone assistance for correct installation of the machine and	
- Humidity and temperature probe			training on the basic use of the panel control (phone date to be	
- USB door + micro SD			agreed in advance)	

ACCESSORIES for KLIMA MEAT VISION

MODEL	DESCRIPTION .
KVISGUI	Pair s/s rails for model VISION
KVISGRI	S/s fridge rack for model VISION
PH205 T	External pH tester with penetration probe
200GSMB	Monitoring and supervisory system – Expert GSM – Automatic alarm call in case of anomalies during processes – Battery included – SIM card NOT included
ASS01	Phone assistance for further training on the panel control
FREQUENCY 60 H	Changing the cabinet's frequency from 50 to 60Hz implies a 5% increase of the gross price



